



**MATERIAL:**  
 BODY: STAINLESS STEEL  
 CONTACT: BERYLLIUM COPPER  
 INSULATOR: PE I

**PERFORMANCE:**  
 IMPEDANCE: 50 OHMS  
 FREQUENCY: DC TO 18GHz  
 VSWR: ≤1.10

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :	XX ±0.20	ANGULAR: ±1°	DEBURR AND BREAK SHARP EDGES
	XXX ±0.10	FILLETS R/C: ±0.10	
	X.XXX ±0.01	SURFACE FINISH: Ra 1.6	
DRAWN	X.C.W	DATE	SIGNATURE
CHKD	H.Z.Y	11/24/2022	
APPRVD	H.Z.Y	11/24/2022	
MFG			
PROJECTION		SIZE	A3
		SCALE	4:1

**LANJIAN ELECTRONICS**  
 38 Hengtong Road, Xinqu Dingmao  
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE  
**NMD3.5/N-JJ**

DWG No. GCPZ3.640.D.037  
 DO NOT SCALE THE DRAWING

REV. A  
 1 / 1