



**MATERIAL:**  
 BODY: STAINLESS STEEL/BRASS  
 CONTACT: BERYLLIUM COPPER  
 INSULATOR: PEI

**PERFORMANCE:**  
 IMPEDANCE: 50 OHMS  
 FREQUENCY: DC TO 110 GHZ  
 VSWR:  $\leq 1.60$

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :		ANGULAR : $\pm 1^\circ$	
XX	$\pm 0.20$	XX	$\pm 0.10$
XXX	$\pm 0.10$	XXX	$\pm 0.10$
XXXX	$\pm 0.01$	XXXX	$\pm 0.01$
SURFACE FINISH : Ra 1.6		DEBURR AND BREAK SHARP EDGES	
NAME	DATE	NAME	SIGNATURE
DRAWN X.C.W	12/12/2022		
CHKD H.Z.Y	12/12/2022		
APPRVD H.Z.Y	12/12/2022		
MFG			
PROJECTION	SIZE	SCALE	
	A3	6:1	

**LANJIAN ELECTRONICS**  
 38 Hengtong Road, Xinqu Dingmao  
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE  
**A1.0-JK-XXdB**  
 Fixed Attenuators

DWG No. \_\_\_\_\_

DO NOT SCALE THE DRAWING

REV. A

DATE 1 / 1