



MATERIAL:
 BODY: STAINLESS STEEL
 CONTACT: BERYLLIUM COPPER
 INSULATOR: NORYL/PTFE

PERFORMANCE:
 IMPEDANCE: 50 OHMS
 FREQUENCY: DC TO 18GHz
 VSWR: ≤1.20

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :		ANGULAR : ±1°	
XX	±0.20	FILETS R/C :	±0.10
XXX	±0.10	SURFACE FINISH :	Ra 1.6
XXXX	±0.01	DEBURR AND BREAK SHARP EDGES	
DRAWN	X.C.W	NAME	DATE
CHKD	H.Z.Y		04/13/2021
APPRVD	H.Z.Y		04/13/2021
MFG			
PROJECTION		SIZE	SCALE
		A3	8:1

LANJIAN ELECTRONICS
 38 Hengtong Road, Xinqu Dingmao
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE
2.92/N-JJ

DWG No. GCP Z3, 640, C, 052

DO NOT SCALE THE DRAWING

REV. A
 1 / 1

