



MATERIAL:
 BODY: STAINLESS STEEL
 CONTACT: BERYLLIUM COPPER
 INSULATOR: PEI

PERFORMANCE:
 IMPEDANCE: 50 OHMS
 DC TO 40 GHZ
 FREQUENCY: ≤1.20

STAINLESS STEEL
 BERYLLIUM COPPER
 PEI

50 OHMS
 DC TO 40 GHZ
 ≤1.20

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :		ANGULAR : ±1°	
XX	±0.20	FILETS R/C :	±0.10
XXX	±0.10	SURFACE FINISH :	Ra 1.6
XXXX	±0.01	DEBURR AND BREAK SHARP EDGES	
NAME	DATE	SIGNATURE	
DRAWN X.C.W	09/13/2021		
CHKD H.Z.Y	09/13/2021		
APPRVD H.Z.Y	09/13/2021		
MFG			
PROJECTION	SIZE	SCALE	
	A3	5:1	

LANJIAN ELECTRONICS
 38 Hengtong Road, Xinqu Dingmao
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE
2.4/3.5-KJ
 straight adaptor

DWG No. GCP Z3.640.0.006
 DO NOT SCALE THE DRAWING

REV.
 A
 1 / 1