



**MATERIAL:**  
 BODY: STAINLESS STEEL  
 CONTACT: BERYLLIUM COPPER  
 INSULATOR: PEI

**PERFORMANCE:**  
 IMPEDANCE: 50 OHMS  
 DC TO 110 GHZ  
 FREQUENCY: ≤1.50

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :  
 UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM

TOLERANCES :	XX ±0.20	ANGULAR : ±1°	DEBURR AND BREAK SHARP EDGES
	XXX ±0.10	FILLETS R/C : ±0.10	
	X.XXX ±0.01	SURFACE FINISH : Ra 1.6	
DRAWN	X.C.W	DATE	SIGNATURE
CHKD	H.Z.Y	08/17/2022	
APPRVD	H.Z.Y	08/17/2022	
MFG			

<p><b>LANJIAN ELECTRONICS</b>          38 Hengtong Road, Xinqu Dingmao          Zhenjiang, 212009, Jiangsu, P. R. China</p>	
<p>TITLE  <b>1.0-J031SR</b></p>	
DWG No.	GCPZ3.650.V.014
REV.	A
DATE	1 / 1

DO NOT SCALE THE DRAWING



SIZE  
 A3

SCALE  
 15:1

