



**MATERIAL:**  
 BODY: STAINLESS STEEL  
 CONTACT: BERYLLIUM COPPER  
 INSULATOR: NORYL

**PERFORMANCE:**  
 IMPEDANCE: 50 OHMS  
 DC TO 18GHZ  
 FREQUENCY: ≤1.20

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :		ANGULAR: ±1°	
XX	±0.20	XX	FILLETS R/C: ±0.10
XXX	±0.10	XXX	SURFACE FINISH: Ra 1.6
XXXX	±0.01	XXXX	DEBURR AND BREAK SHARP EDGES
DRAWN	X.C.W	DATE	SIGNATURE
CHKD	H.Z.Y	08/25/2020	
APPRVD	H.Z.Y	08/25/2020	
MFG			
PROJECTION	SIZE	SCALE	
	A3	8:1	

**LANJIAN ELECTRONICS**  
 38 Hengtong Road, Xinqu Dingmao  
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE  
**SMA/TNC-JK**

DWG No. GCP ZJ.640.A.045  
 DO NOT SCALE THE DRAWING

REV.  
 A  
 1 / 1