



MATERIAL:
 BODY: STAINLESS STEEL
 CONTACT: BERYLLIUM COPPER
 INSULATOR: PEI
PERFORMANCE:
 IMPEDANCE: 50 OHMS
 FREQUENCY: DC TO 26.5GHZ
 VSWR: ≤1.25

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :		ANGULAR: ±1°	
XX	±0.20	FILETS R/C:	±0.10
XXX	±0.10	SURFACE FINISH :	Ra 1.6
X.XXX	±0.01	DEBURR AND BREAK SHARP EDGES	
DRAWN	X.C.W	DATE	SIGNATURE
CHKD	H.Z.Y	11/24/2022	
APPRVD	H.Z.Y	11/24/2022	
MFG			

PROJECTION	SIZE	SCALE
	A3	4:1

LANJIAN ELECTRONICS
 38 Hengtong Road, Xinqu Dingmao
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE
3.5-JK-700

DWG No. GCPZ3.640.F.032

DO NOT SCALE THE DRAWING

REV. A
 1 / 1