



MATERIAL:
 BODY: STAINLESS STEEL
 CONTACT: BERYLLIUM COPPER
 INSULATOR: PEI

PERFORMANCE:
 IMPEDANCE: 50 OHMS
 FREQUENCY: DC TO 50 GHZ
 VSWR: ≤1.35

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL : UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM		TOLERANCES : XX ±0.20 XXX ±0.10 X.XXX ±0.01		ANGULAR : ±1° FILLETS R/C : ±0.10 SURFACE FINISH : Ra 1.6		DEBURR AND BREAK SHARP EDGES	
DRAWN	X.C.W	DATE	10/26/2021	NAME		DATE	
CHKD	H.Z.Y	DATE	10/26/2021	NAME		DATE	
APPRVD	H.Z.Y	DATE	10/26/2021	NAME		DATE	
MFG		DATE		NAME		DATE	
PROJECTION		SIZE	A3	SCALE	5:1		

LANJIAN ELECTRONICS
 38 Hengtong Road, Xinqu Dingmao
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE
2.4-EDGE LAUNCH

DWG No. GCP Z3, 660, 0.037
 DO NOT SCALE THE DRAWING

REV.
 A
 1 / 1