



**MATERIAL:**  
 BODY: STAINLESS STEEL  
 CONTACT: BERYLLIUM COPPER  
 INSULATOR: NORYL /PTFE

**PERFORMANCE:**  
 IMPEDANCE: 50 OHMS  
 DC TO 18GHZ  
 FREQUENCY: ≤1.20

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :		ANGULAR : ±1°	
X.X	±0.20	X.XX	FILETS R/C : ±0.10
X.XX	±0.10	X.XXX	SURFACE FINISH : Ra 1.6
X.XXX	±0.01		DEBURR AND BREAK SHARP EDGES
DRAWN	X.C.W	DATE	SIGNATURE
CHKD	H.Z.Y	09/15/2020	
APPRVD	H.Z.Y	09/15/2020	
MFG			
PROJECTION	SIZE	SCALE	
	A3	8:1	

**LANJIAN ELECTRONICS**  
 38 Hengtong Road, Xinqu Dingmao  
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE  
**N/SMA-KJ**

DWG No. GCP ZJ.640.A.024

DO NOT SCALE THE DRAWING

REV. A  
 1 / 1