



MATERIAL:
 BODY: STAINLESS STEEL
 CONTACT: BERYLLIUM COPPER
 INSULATOR: NORYL /PTFE
PERFORMANCE:
 IMPEDANCE: 50 OHMS
 DC TO 18GHz
 FREQUENCY: ≤1.20

STAINLESS STEEL
 BERYLLIUM COPPER
 NORYL /PTFE

50 OHMS
 DC TO 18GHz
 ≤1.20

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :		ANGULAR: ±1°	
X.X	±0.20	X.XX	FILETS R/C: ±0.10
X.XX	±0.10	X.XXX	SURFACE FINISH: Ra 1.6
X.XXX	±0.01		
NAME	DATE	DEBURR AND BREAK SHARP EDGES	
DRAWN	X.C.W	09/15/2020	SIGNATURE
CHKD	H.Z.Y	09/15/2020	
APPRVD	H.Z.Y	09/15/2020	
MFG			
PROJECTION	SIZE	SCALE	
	A3	8:1	

LANJIAN ELECTRONICS

38 Hengtong Road, Xinqu Dingmao
 Zhenjiang, 212009, Jiangsu, P. R. China

N/SMA-JK

DWG No.

GCP ZJ.640.A.026

REV.
A

DO NOT SCALE THE DRAWING

1 / 1