



MATERIAL:
 BODY: STAINLESS STEEL
 CONTACT: BERYLLIUM COPPER
 INSULATOR: NORYL /PTFE

PERFORMANCE:
 IMPEDANCE: 50 OHMS
 DC TO 18GHz
 FREQUENCY: ≤1.20

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :		ANGULAR : ±1°	
X.X	±0.20	FILETS R/C :	±0.10
X.XX	±0.10	SURFACE FINISH :	Ra 1.6
X.XXX	±0.01	DEBURR AND BREAK SHARP EDGES	
NAME	DATE	SIGNATURE	
DRAWN X.C.W	09/15/2020		
CHKD H.Z.Y	09/15/2020		
APPRVD H.Z.Y	09/15/2020		
MFG			
PROJECTION	SIZE	SCALE	
	A3	8:1	

LANJIAN ELECTRONICS
 38 Hengtong Road, Xinqu Dingmao
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE
 N/SMA-JJ

DWG No. GCP ZJ.640.A.023
 DO NOT SCALE THE DRAWING

REV. A
 DATE 1 / 1

