



安装孔尺寸

参考标准: GB/T 5964-2008  
 工作电压: 3500V (交流)  
 5000V (直流)  
 接触电阻: 内导体间 3mΩ  
 外导体间 3mΩ  
 绝缘电阻:  $\geq 10^{12} \Omega$   
 机械寿命: 500次

材料/镀层:  
 壳体: 黄铜镀镍  
 内导体: 黄铜镀金  
 绝缘介质: PTFE  
 密封圈: 硅橡胶

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"	MATERIAL :			<b>LANJIAN ELECTRONICS</b> 38 Hengtong Road, Xinqu Dingmao Zhenjiang, 212009, Jiangsu, P. R. China		
	UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM					
	TOLERANCES :			TITLE <b>JSHV-KYD</b> <b>(SHV.M-ZJY)</b>		
	X.X	$\pm 0.20$	ANGULAR : $\pm 1^\circ$			DEBURR AND BREAK SHARP EDGES
	X.XX	$\pm 0.10$	FILLETS R/C : $\pm 0.10$			
X.XXX	$\pm 0.01$	SURFACE FINISH : Ra 1.6				
	NAME	DATE	SIGNATURE	DWG No. _____ REV. <b>A</b> DO NOT SCALE THE DRAWING PAGE 1 / 1		
DRAWN	X.C.W	12/16/2021				
CHK'D	H.Z.Y	12/16/2021				
APP'V'D	H.Z.Y	12/16/2021				
MFG						
PROJECTION		SIZE	SCALE			
		A3	5:1			