



MATERIAL:
 BODY: BERYLLIUM COPPER
 CONTACT: BERYLLIUM COPPER
 INSULATOR: PTFE
PERFORMANCE:
 IMPEDANCE: 50 OHMS
 FREQUENCY: DC TO 40 GHz
 VSWR: ≤1.40

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :		ANGULAR : ±1°	
X.X	±0.20	FILLET'S R/C : ±0.10	
X.XX	±0.10	SURFACE FINISH : Ra 1.6	
X.XXX	±0.01	EDGES	
NAME	DATE	SIGNATURE	
DRAWN X.C.W	04/28/2021		
CHKD H.Z.Y	04/28/2021		
APPRVD H.Z.Y	04/28/2021		
MFG			
PROJECTION	SIZE	SCALE	
	A3	8:1	

LANJIAN ELECTRONICS
 38 Hengtong Road, Xinqu Dingmao
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE
SMP-K047R-40G

DWG No. GCPZ3.660.G.024

DO NOT SCALE THE DRAWING

