



**MATERIAL:**  
 BODY: BERYLLIUM COPPER  
 CONTACT: BERYLLIUM COPPER  
 INSULATOR: PEI

**PERFORMANCE:**  
 IMPEDANCE: 50 OHMS  
 FREQUENCY: DC TO 40 GHz  
 VSWR: ≤1.45

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL : UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM		TOLERANCES :		ANGULAR : ±1°		DEBURR AND BREAK SHARP EDGES	
X.X ±0.20		X.XX ±0.10		X.XXX ±0.01		FILLET'S R/C : ±0.10	
NAME		DATE		SIGNATURE			
DRAWN X.C.W		06/14/2022					
CHKD H.Z.Y		06/14/2022					
APPRVD H.Z.Y		04/16/2022					
MFG							
PROJECTION		SIZE		SCALE			
		A3		16:1			

**LANJIAN ELECTRONICS**  
 38 Hengtong Road, Xinqu Dingmao  
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE  
**SMPM-K-FZ-1**

DWG No. GCDZ3.660.H.011

DO NOT SCALE THE DRAWING

REV.  
 A  
 1 / 1