



**MATERIAL:**  
 BODY: STAINLESS STEEL  
 CONTACT: BERYLLIUM COPPER  
 INSULATOR: PE I

**PERFORMANCE:**  
 IMPEDANCE: 50 OHMS  
 FREQUENCY: DC TO 26.5GHZ  
 VSWR: ≤1.25

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :		ANGULAR : ± 1°	
XX	± 0.20	FILETS R/C :	± 0.10
XXX	± 0.10	SURFACE FINISH :	Ra 1.6
X.XXX	± 0.01	DEBURR AND BREAK SHARP EDGES	
DRAWN	X.C.W	DATE	10/28/2022
CHKD	H.Z.Y	DATE	10/28/2022
APPRVD	H.Z.Y	DATE	10/28/2022
MFG		DATE	
PROJECTION		SCALE	10:1
SIZE	A3		

**LANJIAN ELECTRONICS**  
 38 Hengtong Road, Xinqu Dingmao  
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE  
**3.5-KK**

DWG No. GCPZ3.640.F.003  
 REV. A

DO NOT SCALE THE DRAWING  
 1 / 1