



**MATERIAL:**  
 BODY: BERYLLIUM COPPER  
 CONTACT: BERYLLIUM COPPER  
 INSULATOR: PEI  
**PERFORMANCE:**  
 IMPEDANCE: 50 OHMS  
 FREQUENCY: DC TO 65 GHz  
 VSWR:  $\leq 1.25$  (DC TO 40 GHz)  
 $\leq 1.35$  (40 TO 65 GHz)

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :	XX $\pm 0.20$	ANGULAR : $\pm 1^\circ$	DEBURR AND BREAK SHARP EDGES
	XXX $\pm 0.10$	FILLETS R/C : $\pm 0.10$	
	X.XXX $\pm 0.01$	SURFACE FINISH : Ra 1.6	
DRAWN	X.C.W	DATE	SIGNATURE
CHKD	H.Z.Y	07/27/2023	
APPRVD	H.Z.Y	07/27/2023	
MFG			
PROJECTION		SIZE	SCALE
		A3	15:1

**LANJIAN ELECTRONICS**  
 38 Hengtong Road, Xinqu Dingmao  
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE  
**SMPM-KK-700**

DWG No. GCPZ3.640.H.005  
 DO NOT SCALE THE DRAWING

REV. B  
 1 / 1