



**MATERIAL:**  
 BODY: STAINLESS STEEL  
 CONTACT: BERYLLIUM COPPER  
 INSULATOR: PEI

**PERFORMANCE:**  
 IMPEDANCE: 50 OHMS  
 DC TO 40 GHZ  
 FREQUENCY: ≤1.25

**MATERIAL:**  
 UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM

**TOLERANCES:**  
 X.X ±0.20 ANGULAR: ±1°  
 X.XX ±0.10 FILETS R/C: ±0.10  
 X.XXX ±0.01 SURFACE FINISH: Ra 1.6

**DEBURR AND BREAK SHARP EDGES**

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

PROJECTION	SIZE	SCALE
	A3	8:1
DRAWN	X.C.W	DATE
CHKD	H.Z.Y	08/17/2022
APPRVD	H.Z.Y	08/17/2022
MFG		
NAME	DATE	SIGNATURE

**LANJIAN ELECTRONICS**  
 38 Hengtong Road, Xinqu Dingmao  
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE  
**1.0/2.92-JJ**

DWG No. GCPZ3.640.V.023

DO NOT SCALE THE DRAWING

REV. A  
 1 / 1