



MATERIAL:
BODY: STAINLESS STEEL PER AMS-5640,
 ALLOY UNS S30300
CONTACT: BERYLLIUM COPPER PER ASTM B196.
 ALLOY NO. UNS C17300
INSULATOR: PEI
PERFORMANCE:
IMPEDANCE: 50 OHMS
FREQUENCY: DC TO 67 GHz (图示8.3长度范围内)
VSWR: ≤1.20 (背靠背测试后开根号)
IL: ≤0.40 dB (背靠背测试后除以2)

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :			
UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM			
TOLERANCES :			
X.X	±0.20	ANGULAR : ±1°	DEBURR AND BREAK SHARP EDGES
X.XX	±0.10	FILLETS R/C : ±0.10	
X.XXX	±0.01	SURFACE FINISH : Ra 1.6	
	NAME	DATE	SIGNATURE
DRAWN	Y.J.	11/07/2019	
CHK'D	X.C.W	11/07/2019	
APPV'D	X.C.W	11/07/2019	
MFG			
PROJECTION		SIZE	SCALE
		A3	6:1

LANJIAN ELECTRONICS
 38 Hengtong Road, Xinqu Dingmao
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE
 1.85-KFD4-127064P
 jack connector

DWG No.	REV. A
DO NOT SCALE THE DRAWING	
PAGE 1 / 1	